

~~UNCLASSIFIED~~

RECORD CENTER FILE

DOCUMENT NO.

DUN-2530

SERIES AND COPY NO.

DATE

May 24, 1967

(CLASSIFICATION)

DECLASSIFIED

DOUGLAS UNITED NUCLEAR, INC.

RICHLAND, WASHINGTON

Box 26960

RESTRICTED

THIS DOCUMENT CONTAINS RESTRICTED DATA AS DEFINED IN EXECUTIVE ORDER 11652, ITS TRANSMISSION OR THE DISCLOSURE OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED.

TITLE

2.1 E-N DEMONSTRATION LOAD

OTHER OFFICIAL CLASSIFIED INFORMATION
THIS MATERIAL CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE SPY LAWS, TITLE 18, U.S.C. AND 79, THE TRANSMISSION OR DISCLOSURE OF SUCH INFORMATION IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

AUTHOR

L. H. Rice

CIRCULATING COPY
RECEIVED 700 AREA
MAY 26 1967
RETURN TO
DOUGLAS UNITED NUCLEAR, INC.
DOCUMENT CONTROL CENTER

THIS DOCUMENT MUST NOT BE LEFT UNATTENDED OR WHERE AN UNAUTHORIZED PERSON HAS ACCESS TO IT. WHEN NOT IN USE, IT MUST BE STORED IN AN APPROVED SECURE REPOSITORY WITHIN AN APPROVED GUARDED AREA. WHILE IT IS YOUR POSSESSION, YOU HAVE OBTAINED A SIGNED RECEIPT FROM CLASSIFIED FILES, IT IS YOUR RESPONSIBILITY TO KEEP IT AND ITS CONTENTS WITHIN THE LIMITS OF THIS PROJECT AND FROM AN UNAUTHORIZED PERSON. ITS TRANSMITTAL TO, AND STORAGE AT YOUR PLACE OF RESIDENCE IS PROHIBITED. IT IS NOT TO BE DUPLICATED. IF ADDITIONAL COPIES ARE REQUIRED, OBTAIN THEM FROM THE RELATED ISSUING FILE. ALL PERSONS READING THIS DOCUMENT ARE REQUESTED TO SIGN IN THE SPACE PROVIDED BELOW.

ROUTE TO:	PAYROLL NO.	LOCATION	FILES ROUTE DATE	SIGNATURE AND DATE
D. U. N. Record	51532	3763	6-27-67	10/20/67

BEST AVAILABLE COPY

APPROVED FOR
PUBLIC RELEASE

10/2/95

CLASSIFICATION CANCELLED
DATE 5-19-83
For the U.S. Atomic Energy Commission
10/2/95

DUN RECORDS DISPOSITION

Indefinite Retention

Destruction Date

Authority

Until facility is abandoned
13-5-2

SPECIAL RE-REVIEW
FINAL DETERMINATION
DECLASSIFICATION CONFIRMED

DECLASSIFIED

SPECIAL RE-REVIEW
FINAL DETERMINATION
Declassification Confirmed
By: [Signature]
Re-Reviewed 3-20-81
Date

By: J. W. Jordan
Re-Reviewed 5-20-81
Date

BY [Signature]
DATE 10/2/95
BY [Signature]
DATE 10/11/95

DATE 10/2/95
DATE 10/11/95

(CLASSIFICATION)

DECLASSIFIED

DUN-2530

This document consists of 48
pages. Rev. No. 11 of 1
containing [redacted]

[redacted]
This document contains restricted data as
defined in [redacted] 54.
Its transmission in any form or by its
content in any manner to an unauthorized
person is prohibited.

E [redacted]
and [redacted]

BEST AVAILABLE COPY

2.1 E-N DEMONSTRATION LOAD

by:

L. H. Rice
Fuels Engineering Subsection
Research & Engineering Section - DUN

May 24, 1967

**APPROVED FOR
PUBLIC RELEASE**

J. Briggs
10/2/95

DISTRIBUTION

- | | |
|-------------------|------------------|
| 1. J. T. Stringer | 6. L. H. Rice |
| 2. K. C. Bowles | 7. G. L. Smith |
| 3. P. A. Carlson | 8. H. F. Tew |
| 4. G. A. Huff | 9. E. A. Weakley |
| 5. D. W. Peacock | 10. DUN File |
| | 11. DUN Record |

Reviewed and Approved for
Public Release by the NSAT
D. J. Namm PNNL ADD
1.21.01 Date

DECLASSIFIED

 **DOUGLAS UNITED NUCLEAR, INC.**


DUN-2530

DISTRIBUTION:

DECLASSIFIED

DATE May 24, 1967

TO J. T. Stringer, Manager
Manufacturing Engineering Subsection
Production Fuels Section

FROM L. H. Rice, Supervisor 
Product Engineering Unit
Fuels Engineering Subsection - R&E

SUBJECT 2.1 E-N DEMONSTRATION LOAD

In preparation for the full core 2.1 E-N load tentatively scheduled for charging in a K Reactor in July 1968, a technical document is being prepared which will serve as a basis for presentations at AEC Headquarters around the middle of next month. This document is to include a comparison of the material and fabrication costs of Li-Al and LiAlO_2 target elements and a discussion of the procurement problems that may be encountered, both of which are to be prepared by people in your organization. The most probable loading pattern is with the targets and drivers in separate tubes, in which case we will use solid targets, and your estimates should be directed principally toward this case. However, there is the possibility that we will use striped loads which will require an I&E Li-Al or LiAlO_2 target. The design of an I&E LiAlO_2 target is not sufficiently firm to provide a basis for estimating; however, we should have an estimate of the cost penalty of using I&E rather than solid Li-Al targets. The relative cost comparisons should be valid for a continuing program as well as for this specific demonstration.

One item that should not be overlooked is the net cost of fabricating the uranium drivers (excluding costs for criticality control which are being developed by a group headed by Austin Hardin). There will be costs incurred in components, sleeves, tooling, etc., and at the same time there will be a substantial savings due to a reduction in the number of standard fuels produced.

The load will require charging of around 15,600 lithium-bearing targets and 62,600 2.1 enriched drivers, and the targets and drivers will displace 132,000 standard elements that would normally be charged in a K Reactor during the period of the demonstration load. The driver element will be very close to the KX (2.1) design already established (drawing number H-3-7350 Rev. 15), and the tentative design and specifications for the Li-Al and LiAlO_2 targets are attached. The target designs are not firm, but any changes should not be of a nature that will substantially effect the fabrication costs or procurement problems. Please identify any items in the


DECLASSIFIED

 **DECLASSIFIED**

-2-

DUN-2530

J. T. Stringer

May 24, 1967

specifications that, if revised, would have a significant effect on costs. We are currently working on these designs and should have better ones in two weeks. Your contributions would be appreciated by June 5.

Please call on us for assistance whenever we can help.

LHR:scc

Attachment

DECLASSIFIED


DECLASSIFIED

-3-

DUN-2530

TENTATIVE SPECIFICATIONS - LITHIUM-BEARING TARGETS

1. Cladding - C-64 Alloy
2. Core Material

	<u>Li-Al</u>		<u>LiAlO₂</u>	
	<u>Min.</u>	<u>Max.</u>	<u>Min.</u>	<u>Max.</u>
w/o Li	2.75	3.45	9.7	10.2
a/o Li-6 (Li Basis)	44.3	Nom.	17.0	19.0
Density			1.94	2.16
Hydrogen - Vol.%		6		
Water - ppm				50
Boron - ppm		2		2
Cadmium - ppm		2		2
Chromium - ppm		200		200
Cobalt - ppm		10		10
Copper - ppm		200		200
Fluorine - ppm				25
Iron - ppm		500		500
Manganese		50		50

3. Target Dimensions

	<u>Solid Li-Al⁽¹⁾</u>	<u>I&E Li-Al⁽¹⁾</u>	<u>Solid LiAlO₂</u>
Dwg. H-3-27060			
Element Length	8.822 ± .070	8.885 ± .075	
Cap Thickness	0.160 min.	0.200 ± .010	
Base Thickness	0.175 ± .020	0.175 ± .020	
Element O.D.	1.593 ± .008	1.600 ± .003	
Element I.D.	0.437 ± .005	---	
Core O.D.	1.503 ± .002	1.390 ± .002	
Core I.D.	0.527 ± .002	0.800 ± .015	
Core Length	8.397 ± .010	8.398 ± .025	
Axial Gap	None	0.112 ± .025	
Can Wall Thickness	0.045 ± .005	0.100 ± .007	
Minimum Support	0.038	0.038	
Height			
Maximum Projected	1.700	1.700	
Diameter			

(1) Li-Al targets require sizing

DECLASSIFIED